

you can
Canon

iPF8100 / iPF9100
Large Format
Print Solutions

Ideal for Photography
and Fine Art

iPF8100 / iPF9100

IDEAL FOR PHOTOGRAPHY AND FINE ART

The imagePROGRAF iPF8100 and iPF9100 are 12-colour pigment ink 44"/60" large format printers delivering jaw-dropping quality, enduring prints, perfect for the Photography and Fine Art Production markets.

Encompassing a twin print head design, the printers deliver:

- Superb quality with 12-colour lightfast pigment inks
- 2,400 x 1,200 dpi reproduction
- Glossy A0 prints in just over 6 minutes
- Smooth colour graduation and scratch resistant prints with reduced graininess and no bronzing.



Built-in colour calibration so no need for external devices.

Continuous performance thanks to ink-tank replacement during printing and selectable high capacity ink tanks 330ml or 700ml.

Borderless printing up to 42" for stunning photographic and fine art prints.



iPF8100

We Speak Image

44 inch	60 inch	2,400 x 1,200dpi	4 pl	12 colours	Up to 31.9 sqm/hr plain paper	Up to 9.6 sqm/hr glossy paper	30,720 nozzles	Borderless Printing	Built-in Colour Calibration
-------------------	-------------------	--------------------------------------	-------------	----------------------	-------------------------------------	-------------------------------------	--------------------------	------------------------	-----------------------------------

- Automatic Skew Correction, Large LCD and ink level displays for ease-of-use.
- Intuitive software including Digital Photo Front Access and Adobe Photoshop Plug-In.
- Create head-turning posters easily with Canon's PosterArtist tool (optional) offering over 1,000 templates and images.
- 80GB HDD as standard.

Class Ink Type	iPF8100: 44-inch, iPF9100: 60-inch LUCIA Pigment ink, 12 colours (MBK, BK, PC, C, PM, M, Y, R, G, B, GY, PGY)
Maximum Print Resolution	2,400 x 1,200 dpi
Printing Speed (A0 Roll, Full Colour Image)	2:12 (Fast)
Plain paper	4:05 (Standard)
Coated Paper	6:29 (Standard)
Photo Glossy Paper	
Dimensions iPF8100 (W x D x H) (mm)	Main unit with Printer Stand and Basket 1,893 x 975 x 1,144
Weight Packaged	Approx. 142kg
Dimensions W x D x H (mm)	Main unit bundled with Printer Stand and Basket in one package (Palett included), 2,080 x 1,060 x 1,226
Weight Main unit (Palett included)	Approx. 226 kg
Weight Stand and Basket	2,080 x 1,060 x 862 mm; Approx. 175 kg
Weight Packaged	1,795 x 863 x 363 mm; Approx. 43 kg
Dimensions iPF9100 (W x D x H) (mm)	Main unit with Printer Stand and Take-Up Unit 2,299 x 766 x 1,144
Weight Packaged	Approx. 164 kg
Dimensions (W x D x H) (mm)	Main unit and Printer Stand in one package (Palett included) 2,490 x 1,060 x 1,242
Weight Power Supply	Approx. 248 kg
Input power	AC 100 - 240 V (50/60 Hz)
Power consumption	190 W or less
Standby power consumption (At the low power mode)	100 V - 120 V - 5 W or less (when IEEE1394 is mounted, 10 W or less)
Power off (standby)	220 V - 240 V - 6 W or less (when IEEE1394 is mounted, 11 W or less)
Operational Environment	1 W or less (In compliance with Executive Order of the President of the United States of America)
Temperature	15 - 30°C, Humidity: 10 - 80 % (Condensation free)
Acoustic Noise	
Acoustic pressure	iPF8100: Operation: 50 dB (A) or less, Standby: 35 dB (A) or less
Acoustic power	iPF9100: Operation: 51 dB (A) or less, Standby: 35 dB (A) or less
Operation Panel Display	iPF8100: Operation: 6.6 Bels or less
Language on operation panel	iPF9100: Operation: 6.7 Bels or less
Displayable Language on LCD	Large LCD: 160 x 128 dots, Key x 12, LED x 6
Hard Disk	US-English
Printer Language	US-English, French, German, Italian, Spanish, Chinese (simplified), Korean, Japanese (Kanji)
Interface	80GB
USB2.0 Type	GARO
Mode	Hi-Speed
Connector type	Built-in
Ethernet Type	Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer
Standard	Series B (4 pins)
Protocol	IEEE 802.3 10base-T, IEEE 802.3u 100base-TX / Auto-Negotiation, IEEE 802.3 x Full Duplex
IEEE1394 (Option)	IPX/SPX (Netware 3.2(J), 4.1 (J), 4.11(J), 4.2(J), 5.0(J), 5.1(J) SNMP (Canon-MIB), HTTP, TCP/IP, AppleTalk
Type	Slot card type
Standard	IEEE1394 - 1995, P1394a, Half duplex, Data/Strb differential serial
Data-transfer time	100 / 200 / 400 Mbit/sec.
Connector type	In compliance with IEEE1394 - 1995, 6 pins, No power supply
Operating Systems supported	Windows 2000, XP, Server 2003, Vista / Macintosh OS 9, OS X
Regulations	CE Mark, CB Certification, TUV (GS), Gost-R, UL, FCC class B
PRINT HEAD	
Model	PF-03
Type	Bubble-jet on demand
Head configuration	6 colors integrated type (6 chips per print head x 2 print heads)
Nozzle pitch	1,200 dpi x 2
Nozzle per chip	2,560 nozzles per color
Droplet size	4 pl per color
INK TANK	
Model	PFI-301 (330ml) / PFI-701 (700ml) PC, C, PM, M, Y, R, G, B
Model	PFI-302 (330ml) / PFI-702 (700ml) MBK, BK, GY, PGY

MEDIA HANDLING	One Roll, Front-loading, Front Output Front-loading, Front Output (Manual feed using media locking lever)
Roll paper	
Cut sheet	
Media type	Standard Paper 80gsm/90gsm, Matt Coated Paper 90gsm/120gsm/140gsm, Extra Matt Coated Paper 180gsm, Opaque Paper 120gsm, High Resolution Graphic Paper - Self Adhesive 140gsm, High Resolution Barrier Paper 180gsm, Glossy Photo Paper 190gsm/240gsm, Satin Photo Paper 190gsm/240gsm, Inst Dry Paper Glossy 200gsm, Inst Dry Paper Satin 200gsm, Photo Paper High Gloss 255gsm, Photo Paper Semi Matt 255gsm, Photo Paper Pearl 260gsm, Photo Realistic Paper 210gsm, Heavy Weight Glossy Photo Paper 300gsm, Heavy Weight Satin Photo Paper 300gsm, Commercial Proofing Paper 200gsm, Commercial RC Proofing Paper 210gsm/270gsm, Glossy Proofing Paper 195gsm, Semi glossy Proofing Paper 195gsm/255gsm, Art Paper Extra Smooth 250gsm, Prem Art Paper Embossed 225gsm, Prem Art Paper Smooth 225gsm, Scrim Banner, Backlit Film, Universal Opaque Film, Roll-Up Film, Water Resistant Art Canvas, Flame-Resistant Cloth, Adhesive Matt Stretch Vinyl.
Roll paper (width)	ISO: A3, A2, A1, A0, JIS: B2, B0, ARCH: 24", 30", 36" Others: 10", 14", 16", 17", 42", 44", iPF9100: 50", 54", 60"
Cut sheet	ISO: A4, A3, A3+, A2, A1, A0, B4, B3, B2, B1, B0, DIN: C4, C3, C2, C1, C0, JIS: B4, B3, B2, B1, B0, ANSI: 8.5 x 11", 8.5 x 14", 11 x 17", 13 x 19", 17 x 22", 22 x 34", 28 x 40", 34 x 44", ARCH: 9 x 12", 12 x 18", 18 x 24", 24 x 36", 26 x 38", 27 x 39", 30 x 42", 36 x 48", Photo: 20 x 24", 18 x 22", 14 x 17", 12 x 16", 10 x 12", 10 x 15", 8 x 10", 16 x 20" (US Photo size), Poster: 20 x 30", 30 x 40", 42 x 60", 44 x 62", 300 x 900 mm, Others: 13 x 22" Roll paper & Cut sheet: 0.07 - 0.8 mm
Media Thickness	150.0 mm
Maximum Outside Diameter of Roll Paper	Internal diameter of roll core: 2" / 3" (Option)
Media Core Size	iPF8100: Roll paper: 254 - 1,118 mm Cut sheet: 203.2 - 1,117.6 mm
Media Width	iPF9100: Roll paper: 254 - 1,524 mm Cut sheet: 203.2 - 1,524 mm
Minimal Printable Paper Length	203.2 mm
Maximum Printable Paper Length	Roll paper: 18 m (Varies according to the OS and application)
Cut sheet	1.6 m
Margins (Top, Bottom, Sides)	Roll paper: Top: 20 mm, Bottom: 5 mm, Side: 7 mm Cut sheet: Top: 20 mm, Bottom: 23 mm, Side: 7 mm
Recommended area	Roll paper: Top: 5 mm, Bottom: 5 mm, Side: 5 mm Roll paper (borderless print): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet: Top: 5 mm, Bottom: 23 mm, Side: 5 mm
Printable area	
Media width for borderless printing	515 mm (JIS B2), 1,030 mm (JIS B0), 594 mm (ISO A1), 841 mm (ISO A0), 10", 14", 16", 24", 36", 42"
OPTION	
Basket, iPF9100	BU-01
Media Take-up Unit, iPF8100	TU-06
Roll Holder Set (2-inch core spindle)	iPF8100, RH2-42 iPF9100, RH2-63
Roll Holder Set (3-inch core spindle)	iPF8100, RH3-42 iPF9100, RH3-63
IEEE1394 Expansion Board	EB-05
Printer stand	iBF8100 ST-43
CONSUMABLES	
Ink Tank	PFI-301 (330 ml), PFI-701 (700 ml); PC, C, PM, M, Y, R, G, B
Ink Tank	PFI-302 (330 ml), PFI-702 (700 ml); MBK, BK, GY, PGY
Print Head	PF-03
Cutter Blade	CT-06
Maintenance Cartridge	MC-08
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.	
Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.	



Superior print quality only comes with Canon ink and media.

GRAPHIC PRINTING TECHNOLOGIES LTD

you can
Canon

Canon Inc.
www.canon.com

Canon Europa N.V.
www.canon-europe.com

English Edition 0119W394
5026173425162
© Canon Europa N.V., 2008 (0208)

Canon (UK) Ltd
Woodhatch, Reigate
Surrey RH2 8BF
Telephone No: 01737 220000
Facsimile No: 01737 220022
www.canon.co.uk

Canon Ireland
Arena Road, Sandyford Industrial Estate
Dublin 18, Ireland
Telephone No: 01-2052400
Facsimile No: 01-2958141
www.canon.ie

Regus House
268 Bath Road
Slough, Berkshire
SL1 4DX

Tel: +44 (0)1753 727128
Fax: +44 (0)1753 727129
E: info@g-p-t.co.uk
W: www.g-p-t.co.uk