



The SEAL 62 Base provides the following features

Optimum performance

- 1575 mm working width to cope with a wide range of media performance
- Adjustable pressure and speed settings for maximum versatility
- 50 mm nip opening to cover a wide range of substrates
- Heat assisted top roller for superb lamination performance
- 50 mm nip opening suitable for working with a sled for road signs
- 5 m/min max speed for improved productivity
- Manual nip adjustment for precise operation
- Robust, free standing design

Ease of use

- Ergonomic control panel for ease of use
- Auto grip shafts for user friendly webbing
- Swing up feed table to facilitate easy set up

Safety

- Foot switch for hands free operation
- Self checking safety eyes for increased operator safety
- CE certified

The SEAL 62 Base laminator represents SEAL's latest offering to the rapidly moving sign and display market. Ideal for mounting and laminating pressure sensitive solutions up to 1575 mm, this machine represents a flexible package at an affordable price, yet without compromising its functionality.

The SEAL 62 Base is a pressure sensitive machine with heat assist on the top roller to provide superb results with a wide range of materials. Whatever the experience of the operator, the SEAL 62 Base will prove to be a simple machine to use and will deliver genuine flexibility and high performance levels for the small to medium sized end user.

Having great capability delivered at an affordable price, the 62 Base is ideal for signmakers. It will provide the means for these users to finish their images and create more applications thereby generating greater profitability. This laminator is also suitable for small to medium display based businesses who want to provide a wider range of applications and have no need for an encapsulating machine.

The SEAL 62 Base is ideal for producing a wide variety of applications (pressure sensitive materials only)

Rigid Indoor Displays



Floor Graphics



Roll-Up Displays



Backlit Displays



Pop-Up Displays



Rigid Outdoor Displays



SEAL 62 Base

Technical Specifications

Maximum Working Width	1575 mm
Maximum Speed	5 m/min.
Nip pressure	1N/mm
Maximum Substrate Thickness	50 mm
Roller Heating	Heat assisted top roller
Maximum Roller Temperature	40°C
Width	2090 mm
Height	1326 mm
Depth (excl. table)	483 mm
Depth (incl. in-feed table)	590 mm
Working Height	900 mm
Net Weight	240 kg
Width (Shipping Dimensions)	2184 mm
Height	1550 mm
Depth	762 mm
Shipping Weight	300 kg
Electrical Requirements	1N/PE 230VAC +/- 10%, 50/60 Hz, 8,5A
Order Code	64339

Ergonomic control panel for ease of use.



Auto grip shafts for user friendly webbing.



SEAL* is a registered trademark of SEAL Graphics

SEAL Graphics Europe

Heesweg 16A
8102 HJ Raalte
The Netherlands
Tel: + 31 572 346 000
Fax: + 31 572 346 001
Customer services:
Tel: + 49 5722 2070

SEAL Graphics UK Ltd

1 Watkins Close
Burnt Mills Industrial Estate
Basildon, Essex SS13 1TL
United Kingdom
Tel: + 44 1268 722 400
Fax: + 44 1268 725 864

SEAL Graphics Asia

Room 2004-2005, 20th Floor,
Cable TV Tower, 9 Hoi Shing Road,
Tsuen Wan, New Territories
Hong Kong
Tel: + 852 2407 3738
Fax: + 852 2408 0973

SEAL for the Americas

7091 Troy Hill Drive
Elkridge
MD 21075
U.S.A.
Tel: + 1 410 379 5400
Fax: + 1 410 579 8960



Contact your local distributor:



GRAPHIC PRINTING
TECHNOLOGIES LTD

Regus House
268 Bath Road
Slough, Berkshire
SL1 4DX

Tel: +44 (0)1753 727128
Fax: +44 (0)1753 727129
E: info@g-p-t.co.uk
W: www.g-p-t.co.uk

508325/UK/04/2007

www.sealgraphics.com