



### The SEAL 80 Pro provides the following features

#### Optimum performance

- Ergonomic touch pad control panel on a swinging arm enabling operation from the front or rear of the machine
- Output slitters to trim image to size during operation
- Trough to the front of feed table for small rolls of images
- High release silicone rollers for easy cleaning
- Drop-in supply shafts with autogrip for easy loading of materials
- New design for swing up feed table to aid media handling and set-up
- Simple film tension adjustment
- Automatic upper take-up shaft for removing release liners
- Roll-to-roll capability

#### Ease of use

- Adjustable settings for increased capacity and oversatality
- Easy Feed table with built-in tensioning rollers and a flip down image guide for smooth and optimum infeed of media
- Flip-up pull rollers for flutter results when encapsulating and for uninterrupted access when not encapsulating
- Manual nip-adjustment for precision
- 38 mm nip opening for processing a wide range of substrates
- Variable roller technology for better processing of soft substrates
- 2,5n/mm line pressure for superior cold lamination
- Combi-supply shafts for max. flexibility
- Automatic cooling fans for long runs and extended operations

#### Safety

- Foot switch for hands free operation
- Panick strip for operator safety
- Comprehensive safety system with self-checking safety eyes and emergency stops
- CE certified

**The SEAL 80 Pro is a 2 metre wide mounter, laminator and encapsulator based on the already proven design of the SEAL 62 Pro. With fully adjustable temperature, speed and pressure settings the 80 Pro is ideal for the more experienced finisher requiring a highly versatile laminator.**

The SEAL 80 Pro is capable of running a wide range of media and can generate high process speeds, which makes this machine ideal for businesses that are looking to build in extra capacity and more versatility. Capable of mounting, laminating and encapsulating prints up to 2030 mm, the machine can be used with the extensive range of SEAL laminating films, adhesives and substrates.

The 80 Pro features unique design elements such as: an ergonomic touch pad control panel on a swinging arm for ease of use; an Easy Feed table which incorporates built-in tensioning rollers and a flip down image guide for smooth and optimum infeed of media; and outfeed slitters to trim the output to size. These new features maximise the performance and versatility of the 80 Pro without compromising its user friendly nature.

The 80 Pro is ideal for producing a wide variety of applications:

Rigid Indoor Displays



Flexible Indoor Displays



Floor Graphics



Backlit Displays



Pop-Up Displays



Rigid Outdoor Displays



## Technical Specifications

Maximum Working Width	2030 mm
Maximum Speed	6 m/min.
Maximum Substrate Thickness	38 mm
Maximum Roller Temperature	140°C
Roller Heating	Dual
Width	2667 mm
Height	1654 mm
Depth	634 mm
Net Weight	780 kg
Shipping Dimensions	Width 2710 mm
	Height 1690 mm
	Depth 900 mm
Shipping Weight	840 kg
Electrical Requirements	3N/PE 230VAC +/- 10%, 50/60 Hz, 25A
Order Code	64240

SEAL® is a registered trademark of SEAL Graphics

Ergonomic touch pad control panel on a swinging arm.



Easy Feed table with built-in tensioning rollers and a flip down image guide.



Output slitters, cooling fans, flip-up pull rollers.



### SEAL Graphics Europe

Heesweg 16A  
8102 HJ Raalte  
The Netherlands  
Tel: + 31 572 346 000  
Fax: + 31 572 346 001  
Customer services:  
Tel: + 49 5722 2070

### SEAL UK Ltd

1 Watkins Close  
Burnt Mills Industrial Estate  
Basildon, Essex SS13 1TL  
United Kingdom  
Tel: + 44 1268 722 400  
Fax: + 44 1268 725 864

### SEAL Graphics Pacific Ltd

Unit A, 13th Floor, Block 1  
Leader Industrial Centre  
Tsuen Wan, New Territories  
Hong Kong  
Tel: + 852 2407 3738  
Fax: + 852 2408 0973

### SEAL for the Americas

7091 Troy Hill Drive  
Elkridge  
MD 21075  
U.S.A.  
Tel: + 1 410 379 5400  
Fax: + 1 410 579 8960



Contact your local distributor: