



# AquaSEAL SW 3300

## Liquid laminators



The AquaSEAL SW 3300 provides the following features

- Applies durable outdoor coatings for water, abrasion, UV and chemical protection
- Coats media up to 3300 mm wide
- Smooth and consistent coating thickness
- Applies, smoothes and dries coatings
- Automated Infrared curing system
- Segmented heaters to conserve power when running narrow materials
- Fan-folded or roll-fed operation
- Capable of multiple roll handling
- Coated non stick parts for easy cleaning
- Easy fluid application system
- Variable speed control
- Standard with a smooth bar
- CE certified

Now you can increase the profitability of your business with innovative lamination systems designed for superwide output.

SEAL's AquaSEAL family of products offers a superwide laminator that applies smooth and durable liquid laminate coatings for uniform enhancement and protection of your displayed images.

Make the most of your time and energy. Forget manual liquid coating and let this new laminating technology open up new avenues of success for your business.

#### Primary Applications

The AquaSEAL superwide laminator can be used for all wide-format digital printing applications, coating a width up to 3300 mm, including billboards, fleet, and truck curtain sides.

#### AquaSEAL Liquid Laminates

SEAL offers a range of liquids for its AquaSEAL liquid coaters. The AquaSEAL water-based liquid laminates provide maximum protection to a large variety of

indoor and outdoor applications such as billboards, banners and vehicle graphics. The range of liquids consists of economy and premium coatings, both available in gloss and matt finishes. AquaSEAL Economy liquid provides mid-term protection (up to 1-2 years) for UV, water, chemical and abrasion and is ideal for indoor & outdoor banner displays. AquaSEAL Premium liquid provides long-term protection (up to 5 years) and is ideal for use on fleet graphics, outdoor signage and vinyl banners.

AquaSEAL products are recognised internationally by leading printer and substrate manufacturers, including 3M, Avery, Ferrari, Vutek and NUR.

Accucure Feedback system delivering precise control.



# AquaSEAL SW 3300

## Technical Specifications

Maximum Coating Width	3300 mm
Maximum Speed	Up to 3 metres per minute Note: Speed is material and meyer bar dependent
Dimensions (W x D x H)	4000 mm x 1200 mm x 1100 mm
Crated Dimensions (W x D x H)	4300 mm x 1500 mm x 1400 mm
Weight	1134 kg
Warranty	1 year parts
Electrical Requirements	3N/PE 208-240V 50/60Hz 26A per phase Note: Mains cable is not supplied
Compressed Air Requirements	90 - 125 psi Note: Compressor is not supplied Must be ordered separately
Order Code	SW 3300 liquid coater                      60327
Accessories (available to order at additional cost)	Additional Meyer bars #11, #22 and #32 microns are available, Infrared temperature gun, Additional tank, Viscosity cup, AquaClean 170 cleaner, Emergency spare kit
Specifications subject to change without notice.	

User friendly touch sensitive control panel.



Optional dual tank system for easy switching between finishes.



SEAL® and AquaSEAL® are registered trademarks of SEAL Graphics

**NOTE:** Warrantable graphics require the use of a #32 meyer bar. Additional meyer bars that apply less laminate may be purchased at an additional cost.

### SEAL Graphics Europe

Heesweg 16A  
8102 HJ Raalte  
The Netherlands  
Tel: + 31 572 346 000  
Fax: + 31 572 346 001  
Customer services:  
Tel: + 49 5722 2070

### SEAL Graphics UK Ltd

1 Watkins Close  
Burnt Mills Industrial Estate  
Basildon, Essex SS13 1TL  
United Kingdom  
Tel: + 44 1268 722 400  
Fax: + 44 1268 725 864

### SEAL Graphics Pacific Ltd

Unit A, 13th Floor, Block 1  
Leader Industrial Centre  
Tsuen Wan, New Territories  
Hong Kong  
Tel: + 852 2407 3738  
Fax: + 852 2408 0973

### SEAL for the Americas

7091 Troy Hill Drive  
Elkridge  
MD 21075  
U.S.A.  
Tel: + 1 410 379 5400  
Fax: + 1 410 579 8960



Contact your local distributor: