



# Arctic 1000 Series

## Wide Format Professional Series

The Arctic 1040WF<sup>c</sup>, 1064WF<sup>c</sup> and 1064WF<sup>t</sup> are the coolest members of the GBC color finishing line. They are designed to protect and enhance heat-sensitive media. The Arctic 1040WF<sup>c</sup> handles films and adhesives up to 0,965 m wide, while The Arctic 1064WF<sup>c</sup> laminates and mounts with pressure-sensitive films and adhesives up to 1,55 m wide. The 1064WF<sup>t</sup> offers as additional feature a top-heated roller up to 50°C to reduce initial silvering. Production level speeds allow you to finish prints quickly and easily. Use with the GBC Arctic pressure-sensitive line of films and see how "cool" your prints can be!

ARCTIC 1064WF<sup>c</sup> /  
ARCTIC 1064WF<sup>t</sup>



ARCTIC 1040WF<sup>c</sup>

## Features and Benefits

### Easy To Use & Versatile

- Convenient motor-driven rewind for release liner, with brake adjustment.
- Adjustable speed for operator comfort.
- Removable front feed table facilitates changing film rolls.
- Foot pedal allows hands-free operation (not applicable for GBC 1040WF<sup>c</sup>).
- Stand rolls easily for maximum mobility.
- Print baskets catch output and store film (not applicable for GBC 1040WF<sup>c</sup>).
- Reversible motor clears feed jams.
- Roller gap adjusts up to 1,27 cm for mounting.



Arctic 1064 features heavy-duty core chucks.

### Safety

- A disruption of the photo beam stops the rollers to protect fingers from getting caught.
- An emergency stop button is conveniently located to quickly stop the laminator and provide maximum operator control.

### Superior Quality

- Large diameter, easy-to-clean silicone rollers provide a high degree of pressure to create clear output.
- Heavy-duty supply shaft reduces roll deflection (not applicable for GBC 1040WF<sup>c</sup>).

## Specifications

Core diameter:	7,62 cm
Unwind/rewind:	2 unrolls, 1 rewind
Maximum film width:	Arctic 1040WF <sup>o</sup> : 96,5 cm Arctic 1064WF <sup>o</sup> : 155 cm Arctic 1064WF <sup>t</sup> : 155 cm
Maximum film diameter:	15,2 OD
Material thickness:	Up to 1,27 cm
Maximum speed:	Arctic 1040WF <sup>o</sup> : 3,65 m/min Arctic 1064WF <sup>o</sup> : 5 m/min Arctic 1064WF <sup>t</sup> : 5 m/min
Power requirements:	220V, 10 amp, 50Hz
Dimensions (WxHxD):	Arctic 1040WF <sup>o</sup> : 137,1 cm x 55,8 cm x 54,6 cm Arctic 1064WF <sup>o</sup> : 182,8 cm x 121,9 cm x 67,3 cm Arctic 1064WF <sup>t</sup> : 182,8 cm x 121,9 cm x 67,3 cm
Weight:	Arctic 1040WF <sup>o</sup> : 74,8 kg Arctic 1064WF <sup>o</sup> : 129,2 kg Arctic 1064WF <sup>t</sup> : 128 kg
Safety:	CE Listed

## Films

Arctic<sup>®</sup> Pressure Sensitive Laminates  
Arctic<sup>®</sup> Mounting Adhesives



## Applications



- > Window Graphics
- > Trade Show Displays



- > Rigid Displays
- > Floor Graphics



- > Banners
- > Sidewalk Graphics



- > POP Displays
- > Directional Signage

Visit GBC at [www.gbctfilm.com](http://www.gbctfilm.com)