



The SEAL 62 Plus provides the following features

Optimum performance

- Temperature settings: 50°C, 95°C, 110°C, 120°C
- Automatic cooling fans for efficient film cooling and smooth performance during heat sealing applications
- Pull roller system for tensioning of material for a flat and even finish
- Microprocessor controller for even temperature control

Ease of use

- Touch pad control panel with predefined settings for temperature, speed and substrate thickness
- High release silicone rollers for easy cleaning
- L.E.D. setting indicators
- Swing out supply shafts with unique auto-grip for easy loading and positioning of materials
- Simple film tension adjustment
- Automatic upper take-up shaft for removing release liners
- Swinging in-feed table for easy material loading
- Roll-to-roll option

Safety

- Foot switch for hands free operation
- Comprehensive safety system with emergency stops and self-testing optical safety guard
- CE certified

Other Features

- Sturdy stand alone design with castors and levelling feet
- Quiet mechanical operation
- Anti-static pull rollers to eliminate static build-up

The 62 Plus is SEAL's most successful laminator ever. It offers pre-defined control settings, easy material loading and other user-friendly features that make sure new users will have its operation down to a fine art within minimum time!

Capable of mounting, laminating and encapsulating up to 1575 mm digital prints, the 62 Plus can operate with a wide range of materials, including the popular Stoplight range of films.

When finishing inkjet prints the Jet Guard range is recommended, which operates at lower temperatures than traditional films and are the ideal solution for inkjet prints.

The 62 Plus is ideal for producing a wide variety of applications:


Rigid Indoor Displays



Flexible Indoor Displays



Floor Graphics



Backlit Displays



Pop-Up Displays



Rigid Outdoor Displays



SEAL 62 Plus

Technical Specifications

Maximum Working Width	1575 mm
Maximum Speed	1,8 m/min.
Maximum Roller Opening	25 mm
Maximum Roller Temperature	120°C
Width	2200 mm
Depth (excl. tables)	630 mm
Depth (incl. tables)	762 mm
Height	1220 mm
Net Weight	530 kg
Shipping Weight	580 kg
Electrical Requirements	3N/PE 200-250VAC +/- 10%, 50/60 Hz, 16A
Maximum Power Consumption	7000 Watts

SEAL® is a registered trademark of SEAL Graphics

Touch pad control panel with predefined settings for temperature, speed and substrate thickness.



Swing out supply shafts with unique auto-grip for easy loading and positioning of materials.



Optional roll-to-roll.



SEAL Graphics Europe

Heesweg 16A
8102 HJ Raalte
The Netherlands
Tel: + 31 572 346 000
Fax: + 31 572 346 001
Customer services:
Tel: + 49 5722 2070

SEAL UK Ltd

1 Watkins Close
Burnt Mills Industrial Estate
Basildon, Essex SS13 1TL
United Kingdom
Tel: + 44 1268 722 400
Fax: + 44 1268 725 864

SEAL Graphics Pacific Ltd

Unit A, 13th Floor, Block 1
Leader Industrial Centre
Tsuen Wan, New Territories
Hong Kong
Tel: + 852 2407 3738
Fax: + 852 2408 0973

SEAL for the Americas

7091 Troy Hill Drive
Elkridge
MD 21075
U.S.A.
Tel: + 1 410 379 5400
Fax: + 1 410 579 8960



Contact your local distributor:

