

innovate...lamine

Introducing the new Easymount™ double hot wrap with independently heated top and bottom rollers



EM-1600 DHW



Reverse Feature



Speed Control



Temperature Control

Design

The new Easymount™ combines style with functionality. The design has been enhanced and more features have been added. This professional system is simple yet efficient.

Performance

The EM-1600DHW has heated rollers with a maximum temperature of 130° C . The rollers can be independently heated from 0° C - 130° C or both heated to use hot melt films.

Enhancements

The range now features additional mandrel holders for storing spare rolls of film, a swing out feed tray for hassle free loading and a pressure gauge on the rollers to give perfect results every time.

IDEALLY SUITED FOR

- cold laminates
- mounting prints to boards
- applying vinyls
- application tapes
- applying adhesive films
- vehicle wrapping
- canvas bonding

and many more...

GREAT FOR USE IN

- commercial printers
- copy print shops
- exhibition workshops
- reprographic units
- sign maker shops



EM-1600 DHW

FEATURES

- both top & bottom roller can heat up to 130°C independently
- hot & cold mounting & laminating
- solid construction heavy-duty system
- mount & laminate simultaneously
- single/double hot adjustable roller
- take up mandrel for release liner paper
- variable speed control
- large silicon rollers for even pressure
- reverse mechanism & foot pedal
- low maintenance
- magic eye safety feature

ENHANCED FEATURES

- 50% faster - now up to 3m per minute
- extra mandrels to hold spare rolls of film which saves time when changing rolls
- adjustable castors for levelling on an uneven floor
- bigger feed tray to assist prints feeds
- swing out feed tray and safety guard making mounting onto board and loading the film quicker and hassle free
- pressure gauge on rollers, adjustable on machine to give perfect pressure every time



EM-1600 DHW

NEW improved feature!

Recessed sturdy metal mandrel holders - giving you more space to store even larger rolls



specifications

EM-1600 DHW

approx laminating speed (m/min)	3.2
maximum width (mm)	1600 (62")
mounting thickness (mm)	25
roller diameter (mm)	130
warm-up time (mins)	10
hot roller heater system	internal infrared
laminating temperature (°C)	30-130
speed/temp control	dial keypad
pressure adjustment	manual (with guide)
film core (mm)	75
power supply AC (V-Hz)	220/240-50-60
power consumption (single roller) (W)	2500
power consumption (double roller) (W)	5000
machine dimensions (mm)	2270 x 840 x 680
stand dimensions (mm)	2085 x 660 x 285
machine weight (Kg)	212
stand weight (Kg)	80
warranty (year)	1